# **Product datasheet**





## FRONT PLATE CHANGEOVER **NSX250 VERTICAL ROTARY** HANDLE WIDTH 600/650 5M

03245

- ! Discontinued on: 30 Sept 2022
- ! End-of-service on: 25 Apr 2023

#### Main

Range	Prisma	
Range Of Product	Prisma G Prisma P	
Product Or Component Type	Front plate	
Accessory / Separate Part Category	Installation accessory	
Range Compatibility	Prisma Prisma G enclosure Prisma Prisma P cubicle	
Type Of Front Plate	Cut-out	
Installed Device	Source changeover: fixed NSX100250 source changeover - control: mechanical interlock - vertical installation	
Poles Description	1 x 3P: mounting plate support: NSX100250 source changeover vertical installation 1 x 4P: mounting plate support: NSX100250 source changeover vertical installation 2 x 3P: mounting plate support: NSX100250 source changeover vertical installation 2 x 4P: mounting plate support: NSX100250 source changeover vertical installation	
Operating Position	Vertical	

## Complementary

Enclosure/Cubicle Description	Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Cubicle - width 650 mm depth 400 mm
Connection Position	Front connection Direct connection
Number Of Vertical Modules [50 Mm]	5
Standards	IEC 61439-1 IEC 61439-2
Product Certifications	ASEFA
Material	Steel
Surface Finish	Matt Smooth
Protective Treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Colour	White (RAL 9001)
Height	250 mm
Width	500 mm
Net Weight	0.76 kg
Quantity Per Set	Set of 1

Life Is On Schneider 25 Apr 2024

Functional Unit 650 mm 400 mm Prisma P cubicle source changeover NSX100...250 source

changeover fixed mechanical interlock vertical 3P 2 direct 10

650~mm 400 mm Prisma P cubicle source changeover NSX100...250 source

changeover fixed mechanical interlock vertical 4P 2 direct 10

600 mm Prisma G floor-standing enclosure source changeover NSX100...250 source

changeover fixed mechanical interlock vertical 3P 1 front connection 11

600 mm Prisma G wall-mounted enclosure source changeover NSX100...250 source changeover fixed mechanical interlock vertical 3P 1 front connection 11

600 mm Prisma G floor-standing enclosure source changeover NSX100...250 source

changeover fixed mechanical interlock vertical 4P 1 front connection 11

600 mm Prisma G wall-mounted enclosure source changeover NSX100...250 source

changeover fixed mechanical interlock vertical 4P 1 front connection 11

### **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.0 cm
Package 1 Width	26.0 cm
Package 1 Length	51.0 cm
Package 1 Weight	770.0 g
Unit Type Of Package 2	CAR
Number Of Units In Package 2	10
Package 2 Height	17.0 cm
Package 2 Width	27.0 cm
Package 2 Length	53.0 cm
Package 2 Weight	7.94 kg
Unit Type Of Package 3	P12
Number Of Units In Package 3	30
Package 3 Height	35.0 cm
Package 3 Width	80.0 cm
Package 3 Length	120.0 cm
Package 3 Weight	23.82 kg



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance

<b>⊘</b>	Reach Free Of Svhc
<b>⊘</b>	Toxic Heavy Metal Free
<b>⊘</b>	Mercury Free
<b>⊘</b>	Rohs Exemption Information Yes
<b>Ø</b>	Halogen Free Plastic Parts Product

#### **Certifications & Standards**

Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration  Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile