


Product datasheet

Specifications



PLAIN FRONT PLATE WIDTH 600/650 4M

03804

! Discontinued on: 30 Sept 2022

! End-of-service on: 25 Apr 2023

! Discontinued

Main

Range	Prisma
Range Of Product	Prisma G Prisma P
Product Or Component Type	Front plate
Accessory / Separate Part Category	Installation accessory
Range Compatibility	Prisma Prisma G enclosure Prisma Prisma P cubicle
Type Of Front Plate	Plain
Installed Device	TeSys: fixed TeSys U - horizontal installation Altistart: ATS01N103/106FT Phaseo: LV/LV transformer Enerlin'X: FDM128
Poles Description	9 x 3P: modular rail support: TeSys U horizontal installation

Complementary

Enclosure/Cubicle Description	Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Cubicle - width 650 mm depth 400 mm Pack enclosure - width 555 mm
Number Of Vertical Modules [50 Mm]	4
Standards	IEC 61439-1 IEC 61439-2
Product Certifications	ASEFA
Material	Steel
Surface Finish	Matt Smooth
Protective Treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Colour	White (RAL 9001)
Height	200 mm
Width	500 mm
Net Weight	0.86 kg
Quantity Per Set	Set of 1

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Functional Unit	600 mm Prisma G floor-standing enclosure TeSys TeSys U fixed horizontal 3P 9 direct 4
	600 mm Prisma G wall-mounted enclosure TeSys TeSys U fixed horizontal 3P 9 direct 4
	650 mm 400 mm Prisma P cubicle TeSys TeSys U fixed horizontal 3P 9 direct 4
	600 mm Prisma G floor-standing enclosure Altistart ATS01N103/106FT 19 4
	600 mm Prisma G wall-mounted enclosure Altistart ATS01N103/106FT 19 4
	650 mm 400 mm Prisma P cubicle Altistart ATS01N103/106FT 19 4
	600 mm Prisma G floor-standing enclosure Phaseo LV/LV transformer 4
	600 mm Prisma G wall-mounted enclosure Phaseo LV/LV transformer 4
	650 mm 400 mm Prisma P cubicle Phaseo LV/LV transformer 4
	650 mm 400 mm Prisma P cubicle Enerlin'X FDM128 4 4

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.000 cm
Package 1 Width	20.000 cm
Package 1 Length	50.000 cm
Package 1 Weight	828.000 g
Unit Type Of Package 2	CAR
Number Of Units In Package 2	10
Package 2 Height	16.800 cm
Package 2 Width	22.500 cm
Package 2 Length	52.500 cm
Package 2 Weight	8.480 kg
Unit Type Of Package 3	P12
Number Of Units In Package 3	360
Package 3 Height	104.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	317.280 kg

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency RoHS/REACH

Well-being performance

✓	Reach Free Of Svhc	
✓	Toxic Heavy Metal Free	
✓	Mercury Free	
✓	Rohs Exemption Information	Yes
✓	Halogen Free Plastic Parts Product	

Certifications & Standards

Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile