Product datasheet

Specifications



INSULATED FLEX.BAR 24X5 L1800

04746

Discontinued on: 1 Nov 2020

Discontinued

Main

Range	Prisma
Range Of Product	Prisma P Prisma G
Product Or Component Type	Insulated flexible bar
Product Name	Prisma Prisma G enclosure Prisma Prisma P enclosure
Accessory / Separate Part Category	Current distribution accessory
Standards	IEC 61439-2 IEC 61439-1
Product Certifications	ASEFA

Complementary

Installation Description	Cubicle Floor-standing enclosure Wall-mounted enclosure
[Ie] Rated Operational Current	400 A
[In] Rated Current	400 A
Busbar Cross Section	24 x 5 mm
Length	1800 mm
Net Weight	2.48 kg
Quantity Per Set	Set of 1

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2 cm
Package 1 Width	11 cm
Package 1 Length	192 cm
Package 1 Weight	2.480 kg

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO_2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Transparency

RoHS/REACh

Well-being performance

Reach Free Of Svhc	
Toxic Heavy Metal Free	
Mercury Free	
Rohs Exemption Information	Yes

Certifications & Standards

Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile