
Product datasheet

Specifications





INSULATED FLEX.BAR 32X5 L1800

04751

() Discontinued on: 31 Mar 2022

(!) End-of-service on: 30 Nov 2021

<u>()</u> Discontinued

Price: 179,850.00 NGN

Main

Range	Prisma
Range Of Product	Prisma G Prisma P
Product Or Component Type	Insulated flexible bar
Product Name	Prisma Prisma G enclosure Prisma Prisma P enclosure Prisma Prisma iPM L enclosure Prisma Prisma iPM M enclosure
Accessory / Separate Part Category	Current distribution accessory
Standards	IEC 61439-2 IEC 61439-1
Product Certifications	ASEFA

Complementary

Installation Description	Cubicle Floor-standing enclosure Wall-mounted enclosure
[le] Rated Operational Current	520 A
[In] Rated Current	520 A
Busbar Cross Section	32 x 5 mm
Length	1800 mm
Net Weight	3.38 kg
Quantity Per Set	Set of 1

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2 cm
Package 1 Width	11 cm
Package 1 Length	192 cm
Package 1 Weight	3.250 kg

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free

Yes

Certifications & Standards

Rohs Exemption Information

Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
	Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile