

Product datasheet

Specifications



mini Kaedra - for modular device - 1 openings - 6 modules - 1 terminal block

13958

 **Discontinued on:** 31 Dec 2023

 **Discontinued**

Main

Range	Kaedra
Product Or Component Type	Weatherproof enclosure
Enclosure Type	Mini enclosure for modular device
Accessories Included With Enclosure	1 marking kit 1 terminal block 8 holes 1 terminal block support
Mounting Plate Description	Slotted

Complementary

Enclosure Mounting	Surface
9 Mm Pitches	12
Number Of 18 Mm Modules Per Row	6
Total Number Of 18 Mm Modules	6
Number Of Horizontal Rows	1
Electrical Insulation Class	Class II Double insulation
Provided Equipment	1 marking kit 1 terminal block 8 holes 1 terminal block support
Type Of Front Cover	Transparent
Power Dissipation In W	11 W
[In] Rated Current	63 A
Type Of Rail	DIN
Number Of Pre-Cutouts Pg Iso	3
Number Of Terminal Blocks	1 with 8 outgoers
Distribution Block Outgoers	4 x 10 mm ² 4 x 16 mm ²
Locking Options Description	Optional keylock
Enclosure Material	Self-extinguishing polymer
Width	159 mm
Height	200 mm
Depth	112 mm
Internal Depth	56 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Colour	Door: transparent green Enclosure: light grey (RAL 7035)
--------	---

Environment

Standards	IEC 60439-3 EN 50102 IEC 60529 IEC 670 EN 50262
Fire Resistance	750 °C conforming to IEC 60695-2-1
Ip Degree Of Protection	IP65 conforming to IEC 60529
Ik Degree Of Protection	IK09 conforming to EN 50102
Environmental Characteristics (Uv)	UV resistant: class 3 conforming to ISO 4582:2010 Ultraviolet degradation test conforming to ISO 4892-2:2013
Overvoltage Category	II
Ambient Air Temperature For Operation	-25...60 °C

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	11.150 cm
Package 1 Width	16.000 cm
Package 1 Length	20.000 cm
Package 1 Weight	586.000 g
Unit Type Of Package 2	BB1
Number Of Units In Package 2	7
Package 2 Height	22.000 cm
Package 2 Width	34.500 cm
Package 2 Length	40.500 cm
Package 2 Weight	4.374 kg
Unit Type Of Package 3	P12
Number Of Units In Package 3	168
Package 3 Height	80.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	119.880 kg

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

 Mercury Free	
 Rohs Exemption Information	Yes
Reach Regulation	REACH Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information