Product datasheet

Specifications





circuit breaker Masterpact NW25H2 - 2500 A - 4 poles drawout - w/o trip unit

48307

Price: 15,920,647.67 NGN

Main

Product Name MasterPact NW Circuit Breaker Name MasterPact NW25H2 Product Or Component Type Circuit breaker Device Application Power distribution protection Poles Description 4P Neutral Position Left Control Unit Without control unit [In] Rated Current 2500 A at 40 °C Performance Type H2 100 kA 440 V AC [Ue] Rated Operational Voltage 690 V AC 50/60 Hz Suitability For Isolation Yes conforming to EN/IEC 60947-2 Selectivity Category Category B Control Type Push-button		
Circuit Breaker Name MasterPact NW25H2 Product Or Component Type Circuit breaker Device Application Power distribution protection Poles Description 4P Neutral Position Left Control Unit Without control unit [In] Rated Current 2500 A at 40 °C Performance Type H2 100 kA 440 V AC [Ue] Rated Operational Voltage 690 V AC 50/60 Hz Suitability For Isolation Yes conforming to EN/IEC 60947-2 Selectivity Category Category B Control Type Push-button	Range	MasterPacT
Product Or Component Type Circuit breaker Device Application Power distribution protection Poles Description 4P Neutral Position Left Control Unit Without control unit [In] Rated Current 2500 A at 40 °C Performance Type H2 100 kA 440 V AC [Ue] Rated Operational Voltage 690 V AC 50/60 Hz Suitability For Isolation Yes conforming to EN/IEC 60947-2 Selectivity Category Category B Control Type Push-button	Product Name	MasterPact NW
Device Application Power distribution protection Poles Description 4P Neutral Position Left Control Unit Without control unit [In] Rated Current 2500 A at 40 °C Performance Type H2 100 kA 440 V AC [Ue] Rated Operational Voltage 690 V AC 50/60 Hz Suitability For Isolation Yes conforming to EN/IEC 60947-2 Selectivity Category Category B Control Type Push-button	Circuit Breaker Name	MasterPact NW25H2
Poles Description 4P Neutral Position Left Control Unit Without control unit [In] Rated Current 2500 A at 40 °C Performance Type H2 100 kA 440 V AC [Ue] Rated Operational Voltage 690 V AC 50/60 Hz Suitability For Isolation Yes conforming to EN/IEC 60947-2 Selectivity Category Category B Control Type Push-button	Product Or Component Type	Circuit breaker
Neutral PositionLeftControl UnitWithout control unit[In] Rated Current2500 A at 40 °CPerformance TypeH2 100 kA 440 V AC[Ue] Rated Operational Voltage690 V AC 50/60 HzSuitability For IsolationYes conforming to EN/IEC 60947-2Selectivity CategoryCategory BControl TypePush-button	Device Application	Power distribution protection
Control Unit Without control unit [In] Rated Current 2500 A at 40 °C Performance Type H2 100 kA 440 V AC [Ue] Rated Operational Voltage 690 V AC 50/60 Hz Suitability For Isolation Yes conforming to EN/IEC 60947-2 Selectivity Category Category B Control Type Push-button	Poles Description	4P
[In] Rated Current 2500 A at 40 °C Performance Type H2 100 kA 440 V AC [Ue] Rated Operational Voltage 690 V AC 50/60 Hz Suitability For Isolation Yes conforming to EN/IEC 60947-2 Selectivity Category Category B Control Type Push-button	Neutral Position	Left
Performance Type H2 100 kA 440 V AC [Ue] Rated Operational Voltage 690 V AC 50/60 Hz Suitability For Isolation Yes conforming to EN/IEC 60947-2 Selectivity Category Category B Control Type Push-button	Control Unit	Without control unit
[Ue] Rated Operational Voltage 690 V AC 50/60 Hz Suitability For Isolation Yes conforming to EN/IEC 60947-2 Selectivity Category Category B Control Type Push-button	[In] Rated Current	2500 A at 40 °C
Suitability For Isolation Yes conforming to EN/IEC 60947-2 Selectivity Category Category B Control Type Push-button	Performance Type	H2 100 kA 440 V AC
Selectivity Category Category B Control Type Push-button	[Ue] Rated Operational Voltage	690 V AC 50/60 Hz
Control Type Push-button	Suitability For Isolation	Yes conforming to EN/IEC 60947-2
• • • • • • • • • • • • • • • • • • •	Selectivity Category	Category B
Mounting Mode Drawout	Control Type	Push-button
	Mounting Mode	Drawout

Complementary

[Icu] Rated Ultimate Short-Circuit Breaking Capacity	100 kA at 220/415 V AC 50/60 Hz 100 kA at 440 V AC 50/60 Hz 85 kA at 525 V AC 50/60 Hz 85 kA at 690 V AC 50/60 Hz
[Ics] Rated Service Breaking Capacity	100 kA at 220/415 V AC 50/60 Hz 100 kA at 440 V AC 50/60 Hz 85 kA at 525 V AC 50/60 Hz 85 kA at 690 V AC 50/60 Hz
[Icw] Rated Short-Time Withstand Current	85 kA 1 s 75 kA 3 s
[Icm] Rated Short-Circuit Making Capacity	220 kA 220/415 V AC at 50/60 Hz 187 kA 440 V AC at 50/60 Hz 187 kA 525 V AC at 50/60 Hz 187 kA 690 V AC at 50/60 Hz
Integrated Instantaneous Protection (Din In Ka Peak)	171209 kA
Sensor Rating	1250 A 2500 A
[Ui] Rated Insulation Voltage	1000 V AC 50/60 Hz
[Uimp] Rated Impulse Withstand Voltage	12 kV

Power Dissipation In W	600 W
Maximum Breaking Time	25 ms
Maximum Closing Response Time	70 ms
Mounting Support	Backplate Rails
Upside Connection	Front Rear
Downside Connection	Front Rear
Connection Pitch	115 mm
Mechanical Durability	10000 cycles without maintenance 20000 cycles with maintenance
Electrical Durability	5000 cycles 440 V AC 50/60 Hz without maintenance conforming to EN/IEC 60947-2 2500 cycles 690 V AC 50/60 Hz without maintenance conforming to EN/IEC 60947-2 AC-23A: 5000 cycles 440 V AC 50/60 Hz without maintenance conforming to EN/IEC 60947-3 AC-23A: 2500 cycles 690 V AC 50/60 Hz without maintenance conforming to EN/IEC 60947-3 AC-3: 6000 cycles 440/690 V AC 50/60 Hz without maintenance conforming to EN/ IEC 60947-3
Height	439 mm
Width	556 mm
Depth	395 mm
Net Weight	120 kg
Standards	EN/IEC 60947-1 EN/IEC 60947-2
Product Certifications	CE CCC EAC

Environment

Ip Degree Of Protection	IP30 conforming to IEC 60529	
Pollution Degree	4 conforming to IEC 60664-1	
Ambient Air Temperature For Operation	-2570 °C	
Ambient Air Temperature For Storage	-4085 °C	
Operating Altitude	02000 m without derating 2000 m5000 m with derating	

Packing Units

-	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	30.5 cm
Package 1 Width	29.5 cm
Package 1 Length	49.5 cm
Package 1 Weight	49.501 kg

Contractual warranty

Warranty

18 months

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free
Rohs Exemption Information Yes
Pvc Free

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information